


DEFERRED MAINTENANCE SWEARINGEN ENGINEERING CENTER MECHANICAL SYSTEMS AND CONTROLS COLUMBIA, SOUTH CAROLINA

Project No. H27-6094-K

UNIVERSITY of SOUTH CAROLINA



SCALE : 1" = 300' - 0"

THE UNIVERSITY OF SOUTH CAROLINA

. DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

DO NOT SCALE DRAWINGS. VERIFY ALL REQUIRED INFORMATION

IN FIELD BY VISITING SITE PRIOR TO SUBMITTING BID.

. WHENEVER THE WORD "PROVIDE" IS USED IT SHALL MEAN FURNISH AND INSTALL COMPLETE AND READY FOR USE.

ALL MATERIALS CALLED FOR TO BE REMOVED SHALL REMAIN THE PROPERTY OF THE OWNER. ANY ITEM THE OWNER DOES NOT WISH TO KEEP SHALL BE REMOVED FROM THE SITE OF WORK.

PROVIDE ALL ITEMS OF MISCELLANEOUS STEEL AS REQUIRED FOR INSTALLATION OF ALL MECHANICAL OR CONTROL COMPONENTS. . PIPING SYSTEMS SHALL BE DRAINED AS REQUIRED FOR INSTALLATION OF WORK.

PROVIDE FOR ACCESS TO ALL MECHANICAL/CONTROL ITEMS REQUIRING CLEANING OR ADJUSTMENT.

INDEX OF DRAWINGS

TITLE SHEET

HYAC FLOOR PLAN - BASEMENT MECH, ROOM ØBØ3, SCHEDULES AND DETAILS M2 | HYAC FLOOR PLAN - FIRST FLOOR MECH. ROOMS 1A30 and 1B05

M3 HYAC FLOOR PLAN - SECOND FLOOR MECH. ROOMS 2A35 and 2B05

M4 HVAC FLOOR PLAN - THIRD FLOOR MECH, ROOMS 3A81 and 3B05

BASEMENT ELECTRICAL DEMOLITION AND RENOVATION PLANS

FIRST FLOOR ELECTRICAL DEMOLITION AND RENOVATION PLANS

E3 | SECOND FLOOR ELECTRICAL DEMOLITION AND RENOVATION PLANS

E4 THIRD FLOOR ELECTRICAL DEMOLITION AND RENOVATION PLANS

MECHANICAL 4403 Broad River Road Columbia, S.C. 29210

DEFERRED MAINTENANCE – SWEARINGEN ENGINEERING CENTER MECHANICAL SYSTEMS AND CONTROLS Project No. H27-6094-K

2 **of** 5

сомм. No. 133000

DRAIN PAN

WATER COIL PIPING DIAGRAM NOT TO SCALE



THREADED CAP

- BOTTOM OF OUTLET -

BOTTOM OF DRAIN -

图 ½ OF DIMENSION A

NOT TO SCALE

TOP OF TRAP -

(A) 1" FOR EACH 1" OF MAXIMUM NEGATIVE STATIC PRESSURE PLUS 1" (3" MINIMUM)

CONDENSATE DRAIN PIPE INSTALLATION DETAIL

NOTE: CONDENSATE DRAIN PIPE SIZE SHALL BE FULL SIZE DRAIN CONNECTION BUT NOT LESS THAN 1" DIAMETER. DRAIN LINE SHALL BE INSULATED TYPE "L" COPPER

C A + B + PIPE DIAMETER (I" MIN)

AIR HANDLING UNIT COIL AND MOTOR SCHEDULE NEW COOLING COIL MARK MAX ENT. AIR LYG. AIR
AIR P.D. FDB FWB FDB FWB

GPM EWT LWT MAX WTR RUNOUT PIPE SIZE EXIST. NEW MOTOR TOTAL SENS. MBH MBH MODEL NUMBER | SERIAL NUMBER 1ST FLR 14,500 CCDB25EEØF K86K14416 C & D WINGS 1ST FLR A WING 5,500 CCDBØ8AEØF K86K144Ø7 134.9 1ST FLR CCDB21BEØF K86K144Ø8 12,500 411.2 326.5 A WING 2ND FLR CCDB3IBEØF K86K14417 18,000 20 (1) C & D WINGS

AH-1.1 381.8 | 0.726 | 79.3 | 64.9 | 55 | 54.3 | 76.1 | 48 | 60 | 10.0 3" 2" AH-1.3 0.863 | 17.8 | 64.5 | 54.1 | 53.4 | 68.3 | 48 | 60 | 12.0 2-1/2" Ø.717 | 78.8 | 64.4 | 55.1 | 54.5 | 89.1 | 48 | 60 | 10.0 3" 2ND FLR 0.871 80.4 65.4 53.3 52.6 43.7 48 60 00 CCDB14BEØF K86K14413 7.5 214.5 2-1/2" A WING 2ND FLR AH-2.3 17,200 CCDB35MEØF K86K14418 531.5 447.1 0659 | 18.3 | 64.4 | 546 | 53.9 | 88.3 | 48 | 60 | 15.1 A WING 3RD FLR 25 (1) 635.2 584.4 AH-3.1 22*,000* CCDB4IRE@G K87BØ2994 0.651 | 19.6 | 64.4 | 55.5 | 54.8 | 105.6 | 48 | 60 | 10.0 3" C & D WINGS 3RD FLR A WING AH-3.2 CCDB2ICE@G K87BØ2994 11,700 326.8 303.4 2-1/2" 3RD FLR 11,200 2-1/2" K87B02772 15 319.3 295.7 0613 | 19.9 | 64.6 | 55.9 | 55.2 | 53.1 | 48 | 60 | 15.0 A WING

(1) REMOVE EXISTING ABB VARIABLE FREQUENCY DRIVE (VFD), AND REPLACE WITH NEW ABB VFD FOR NEW MOTOR SIZE

	PUMP SCHEDULE (1)							
MARK	B & G MODEL 2	GPM	HEAD	RPM	MIN. EFF.	MOTOR H.P.	SERVICE	
P-1	1510	1,300	105'	1750	81.5%	50	SYSTEM PRIMARY	
P-2	1510	1,300	105'	1750	81.5%	50	SYSTEM STANDBY	

DISCHARGE

To Political Pol

CHILLED WATER PUMP DETAIL

B & G TRIPLE DUTY VALVE—— (COMBINATION SHUT-OFF, BALANCING AND CHECK VALVE)

FLEXIBLE CONNECTION ON— SUCTION AND DISCH. PIPES (DOUBLE SPHERE WITH ROOT RING, 150 PSIG RATING), SEE SPECS.

EXISTING INERTIA PAD / PAD ON SPRING ISOLATORS, REPLACE SPRINGS PER SEISMIC SEISMIC SUBMITTALS.

NOT TO SCALE

SUCTION

- EXISTING 8" CHILLED WATER PIPES

BUTTERFLY VALVE

─1/4" QUARTER-TURN BALL VALVE, TYP.

- DRAIN WITH HOSE END CONNECTION.

PROVIDE SPOOL PIECE AS REQUIRED TO ALIGN WITH EXISTING PIPE DROPS

FIN. FLOOR


- SUCTION DIFFUSER W/ STRAINER

REMARKS

- (1) PUMP TO MATCH AVAILABLE ELECTRICAL SERVICE, SEE ELECTRICAL.
- $\left(2
 ight)$ or equal by armstrong, patterson or approved equal, see specifications.
- 3) PROVIDE P-1 and P-2 WITH NEW YARIABLE FREQUENCY DRIVES.
- (4) BRAKE HORSEPOWER SHALL NOT EXCEED 90% OF MOTOR HORSEPOWER.

RENOVATION NOTES REMOVE EXISTING CHILLED WATER PUMP COMPLETE, INCLUDING ASSOCIATED VALVES AND VFD. PROVIDE NEW PUMP, AND VALVES AS SCHEDULED, DETAILED AND SPECIFIED. RE-USE EXISTING PUMP MOTOR VARIABLE FREQUENCY DRIVE.	ELIMBO FLIME EL
EHWS——EHWS——	


HYAC FLOOR PLAN - BASEMENT MECH ROOM ØBØ3



KEY PLAN - BASEMENT


MECHANICAL 4403 Broad River Road Columbia, S.C. 29210 (803) 731-9834 (803) 731-9837 FAX DATE: 01/11/13

SCALE: 1/4" ==== 1'-@"




MECHANICAL 4403 Broad River Road Columbia, S.C. 29210 (803) 731-9834 (803) 731-9837 FAX DATE: 01/11/13 сомм. по. 133000

KEY PLAN - 1ST FLOOR



HYAC FLOOR PLAN - 2ND FLOOR MECH ROOM 2BØ5 SCALE: 1/4" ==== 1'-@"

RENOVATION NOTES




KEY PLAN - 2ND FLOOR


1. PROVIDE RACEWAY AND WIRING TO ALL DEVICES AND EQUIPMENT INDICATED ON THE CONTRACT DRAWINGS. THE DRAWINGS INDICATE PARTIAL RACEWAY AND WIRING REQUIREMENTS TO HELP CLARIFY THE DESIGN INTENT. WHERE RACEWAY AND/OR WIRING IS NOT INDICATED FOR DEVICES OR EQUIPMENT THE ARRANGEMENT. GROUPING, AND ROUTING SHALL BE PROVIDED IN ACCORDANCE WITH THE 2008 NATIONAL ELECTRICAL CODE.

GENERAL CONSTRUCTION NOTES

- 2. VERIFY ACTUAL MOUNTING LOCATIONS AND ARRANGEMENTS OF EQUIPMENT FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR PRIOR TO ELECTRICAL ROUGH—IN. MAKE ADJUSTMENTS TO THE ELECTRICAL WORK AS REQUIRED TO ACCOMMODATE ACTUAL MOUNTING LOCATIONS.
- 3. PROVIDE A GREEN INSULATED GROUND WIRE IN ALL RACEWAYS.
- 4. PROVIDE ADDITIONAL SUPPORTS FOR CONTROL PANELS, SWITCHES, RACEWAYS. AND OTHER ELECTRICAL EQUIPMENT WHEREVER THE BUILDING STRUCTURE IS NOT SUITABLE FOR DIRECT MOUNTING.
- 5. CUTTING, DRILLING, FITTING AND PATCHING: PROVIDE CHASES, SLOTS, AND OPENINGS IN EXISTING BUILDING COMPONENTS TO ALLOW FOR ELECTRICAL INSTALLATIONS. PERFORM CUTTING, DRILLING, FITTING, AND PATCHING REQUIRED TO:
 A) INSTALL EQUIPMENT, MATERIALS, AND RACEWAYS IN EXISTING STRUCTURES.
- B) REMOVE AND REPLACE DEFECTIVE WORK THAT DOES NOT CONFORM TO REQUIREMENTS OF THE CONTRACT DOCUMENTS.
- C) UPON WRITTEN INSTRUCTIONS FOR THE ENGINEER, UNCOVER AND RESTORE WORK TO PROVIDE FOR ENGINEER OBSERVATION OF CONCEALED WORK.
- PATCH EXISTING SURFACES AND BUILDING COMPONENTS USING NEW MATERIALS THAT MATCH EXISTING MATERIALS. PATCHING SHALL BE PERFORMED BY EXPERIENCED
- 6. COORDINATE ALL REQUIRED OUTAGES TO EXISTING ELECTRICAL SERVICES WITH DENNIS GALLAGHER USC ELECTRICAL MAINTENANCE DEPARTMENT.

INSTALLERS.





BASEMENT ELECTRICAL DEMOLITION PLAN

SCALE: 1/8" = 1'-0"

BASEMENT ELECTRICAL RENOVATION PLAN

SCALE: 1/8" = 1'-0"

SHEET:

OF

SHEET IN SET:

BELKA ENGINEERING ASSOCIATES, IN

FIRST FLOOR ELECTRICAL DEMOLITION PLAN

SCALE: 1/8" = 1'-0" (NORTHWEST CORNER OF BUILDING)

EXISTING ARRANGE SPEED
DRIVE - TO REMAN IN PLACE.

EXISTING ARRANGE SPEED
DRIVE - TO REMAN IN PLACE.


EXISTING WITH COUNTY - TO REMAN IN PLACE.

EXISTING WITH COUNTY - TO REMAN IN PLACE.

EXISTING WITH COUNTY - TO REMAN IN PLACE.

FIRST FLOOR ELECTRICAL DEMOLITION PLAN

SCALE: 1/8" = 1'-0" (SOUTHEAST CORNER OF BUILDING)



FIRST FLOOR ELECTRICAL RENOVATION PLAN

SCALE: 1/8" = 1'-0" (NORTHWEST CORNER OF BUILDING)

ELECTRICAL NOTES

D1. AHU-1.1S: EXISTING 20 HORSEPOWER, 480-VOLT FAN MOTOR IS BEING REPLACED UNDER THIS CONTRACT. EXISTING RACEWAYS, 60-AMP 3-POLE CIRCUIT BREAKER IN

R1. AHU-1.1S: PROVIDE THREE #10 AWG THHN CONDUCTORS WITH ONE #10 AWG THHN GREEN GROUND WIRE FROM PANEL "M1C", THROUGH EXISTING FPE STARTER,

D2. AHU—1.3S: EXISTING 15 HORSEPOWER, 480—VOLT FAN MOTOR IS BEING REPLACED UNDER THIS CONTRACT. EXISTING RACEWAYS, 40—AMP 3—POLE CIRCUIT BREAKER IN PANEL "M1A", AND VARIABLE SPEED DRIVE SHALL REMAIN IN PLACE AND SHALL BE RE—USED. DISCONNECT EXISTING FAN MOTOR, FLEXIBLE METAL CONDUIT TO

PECKERHEAD, AND ALL ASSOCIATED POWER CONDUCTORS FROM RACEWAYS (BACK TO

CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT—BOLT SPLICES AND HEAT OR COLD—SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS

R2. AHU-1.3S: PROVIDE THREE #10 AWG THHN CONDUCTORS WITH ONE #10 AWG THHN GREEN GROUND WIRE FROM PANEL "M1A", THROUGH EXISTING FPE STARTER AND VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE

REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY

TYPE BOLTED CONNECTORS SHALL NOT BE USED).

DISCONNECT SWITCH, AND VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT—BOLT SPLICES AND HEAT OR COLD—SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS TYPE BOLTED CONNECTORS SHALL NOT BE USED).

CONDUCTORS FROM RACEWAYS (BACK TO PANELBOARD "M1C").

PANELBOARD "M1A").


PANEL "M1C", DISCONNECT SWITCH, FPE STARTER, AND VARIABLE SPEED DRIVE SHALL REMAIN IN PLACE AND SHALL BE RE-USED. DISCONNECT EXISTING FAN MOTOR, FLEXIBLE METAL CONDUIT TO MOTOR PECKERHEAD, AND ALL ASSOCIATED POWER

SEE NOTE R2—AHU-1,35

NECHMINAL
RECTIONAL
RECT

FIRST FLOOR ELECTRICAL RENOVATION PLAN

SCALE: 1/8" = 1'-0" (SOUTHEAST CORNER OF BUILDING)



BEA EN EN EN ASK

CAMPUS PLANNING AND CONSTRUCTION COLUMBIA, SC 29208

WN BY CAROLINIATH CAROLINIATH

R: DATE: CHECKED BY: CHECKED BY: KLB KLB
CRIPTION DATE ORIG. BY DRAWN E

RING BUILDING: PROJECT NUMBER: 173 H27-6094-K
DLS REV. DESCRIP


NCE – SWEARINGEN ENGINEER SAL SYSTEMS AND CONTRO

FERRED MAINTENANCE - STENTER MECHANICAL SYST

OF
SHEET IN SET:

(NORTHWEST CORNER OF BUILDING)

SECOND FLOOR ELECTRICAL DEMOLITION PLAN E3 SCALE: 1/8" = 1'-0"



SECOND FLOOR ELECTRICAL DEMOLITION PLAN

SCALE: 1/8" = 1'-0" (SOUTHEAST CORNER OF BUILDING)

ELECTRICAL NOTES


- D1. AHU-2.1S: EXISTING 20 HORSEPOWER, 480-VOLT FAN MOTOR IS BEING REPLACED WITH A 25 HORSEPOWER MOTOR UNDER THIS CONTRACT. EXISTING 70-AMP 3-POLE CIRCUIT BREAKER IN PANEL "M2C" AND FPE MOTOR STARTER SHALL REMAIN IN PLACE AND SHALL BE RE-USED. DISCONNECT EXISTING FAN MOTOR, DISCONNECT SWITCH, VARIABLE SPEED DRIVE, AND ALL ASSOCIATED RACEWAYS AND POWER CONDUCTORS (BACK TO PANELBOARD "M2C"). NOTE THAT CONDUCTORS APPEAR TO BE ROUTED THROUGH EXISTING JOHNSON CONTROLS DSC-8500 PANELS - THIS POWER WIRING AND CONDUIT SHALL ALSO BE REMOVED/REPLACED.
- R1. <u>AHU-2.1S</u>:

PROVIDE ONE 60-AMP/3-POLE/480-VOLT/FUSED/NEMA-1 RATED DICONNECT SWITCH TO REPLACE THE EXISTING DISCONNECT SWITCH. FUSES SHALL BE CLASS RK5 AND SHALL BE SIZED PER THE MOTOR MANUFACTURER'S RECOMMENDATIONS. PROVIDE THREE MELTING ALLOY THERMAL UNITS RATED FOR THE 25 HORSEPOWER MOTOR IN THE EXISTING FPE MOTOR STARTER.


INSTALL ONE 25 HORSEPOWER RATED ABB VARIABLE SPEED DRIVE TO REPLACE THE EXISTING 20 HORSEPOWER RATED ABB DRIVE. THE DRIVE SHALL BE FURNISHED BY THE MECHANICAL CONTRACTOR.

PROVIDE THREE #8 AWG THHN CONDUCTORS WITH ONE #10 AWG THHN GREEN GROUND WIRE IN 3/4" RMC CONDUIT FROM PANEL "M2C", THROUGH NEW STARTER, JOHNSON CONTROLS DSC-8500 PANELS, AND VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT-BOLT SPLICES AND HEAT OR COLD-SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS TYPE BOLTED CONNECTORS SHALL NOT BE USED).

- D2. AHU-2.2S: EXISTING 7.5 HORSEPOWER, 480-VOLT FAN MOTOR IS BEING REPLACED UNDER THIS CONTRACT. EXISTING RACEWAYS, 20-AMP 3-POLE CIRCUIT BREAKER IN PANEL "M2C", FPE STARTER, AND VARIABLE SPEED DRIVE SHALL REMAIN IN PLACE AND SHALL BE RE-USED. REMOVE EXISTING FAN MOTOR, FLEXIBLE METAL CONDUIT TO MOTOR PECKERHEAD, AND ALL ASSOCIATED POWER CONDUCTORS FROM RACEWAYS (BACK TO PANELBOARD "M2C"). NOTE THAT CONDUCTORS APPEAR TO BE ROUTED THROUGH EXISTING JOHNSON CONTROLS DSC-8500 PANELS - THIS POWER WIRING SHALL ALSO BE REMOVED/REPLACED.
- R2. AHU-2.2S: PROVIDE THREE #12 AWG THHN CONDUCTORS WITH ONE #12 AWG THHN GREEN GROUND WIRE FROM PANEL "M2C", THROUGH EXISTING FPE STARTER, JOHNSON CONTROLS DSC-8500 PANELS, AND VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT-BOLT SPLICES AND HEAT OR COLD-SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS TYPE BOLTED CONNECTORS SHALL NOT BE USED).
- D3. AHU-2.3S: EXISTING 15 HORSEPOWER, 480-VOLT FAN MOTOR IS BEING REPLACED UNDER THIS CONTRACT. EXISTING RACEWAYS, 40-AMP 3-POLE CIRCUIT BREAKER IN PANEL "M2A", FPE STARTER, AND VARIABLE SPEED DRIVE SHALL REMAIN IN PLACE AND SHALL BE RE-USED. DISCONNECT EXISTING FAN MOTOR. FLEXIBLE METAL CONDUIT TO MOTOR PECKERHEAD, AND ALL ASSOCIATED POWER CONDUCTORS FROM RACEWAYS (BACK TO PANELBOARD "M2A").
- R3. AHU-2.3S: PROVIDE THREE #10 AWG THHN CONDUCTORS WITH ONE #10 AWG THHN GREEN GROUND WIRE FROM PANEL "M2A", THROUGH EXISTING FPE STARTER AND VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT-BOLT SPLICES AND HEAT OR COLD-SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS TYPE BOLTED CONNECTORS SHALL NOT BE USED).



SECOND FLOOR ELECTRICAL RENOVATION PLAN E3 SCALE: 1/8" = 1'-0"(NORTHWEST CORNER OF BUILDING)




SECOND FLOOR ELECTRICAL RENOVATION PLAN (SOUTHEAST CORNER OF BUILDING)

CAMPUS PLANNING AND CONSTRUCTION COLUMBIA, SC 29208


BELKA ENGINEERING ASSOCIATES, INC





NTENANCE – SWEARINGEN ENGINEERING HANICAL SYSTEMS AND CONTROLS

THIRD FLOOR ELECTRICAL DEMOLITION PLAN (NORTHWEST CORNER OF BUILDING)



THIRD FLOOR ELECTRICAL DEMOLITION PLAN (SOUTHEAST CORNER OF BUILDING)

ELECTRICAL NOTES

- D1. AHU-3.1S: EXISTING 20 HORSEPOWER, 480-VOLT FAN MOTOR IS BEING REPLACED WITH A 25 HORSEPOWER MOTOR UNDER THIS CONTRACT. EXISTING 60-AMP 3-POLE CIRCUIT BREAKER IN PANEL "M3C" SHALL BE REMOVED AND REPLACED AS INDICATED IN NOTE R1 BELOW. DISCONNECT EXISTING FAN MOTOR, DISCONNECT SWITCH, VARIABLE SPEED DRIVE, AND ALL ASSOCIATED RACEWAYS AND POWER CONDUCTORS (BACK TO PANELBOARD "M3C").
- R1. <u>AHU-3.1S</u>:

PROVIDE ONE 60-AMP/3-POLE/480-VOLT/FUSED/NEMA-1 RATED DICONNECT SWITCH TO REPLACE THE EXISTING DISCONNECT SWITCH. FUSES SHALL BE CLASS RK5 AND SHALL BE SIZED PER THE MOTOR MANUFACTURER'S RECOMMENDATIONS.

PROVIDE THREE 25-HORSEPOWER RATED MELTING ALLOW THERMAL UNITS IN EXISTING FPE STARTER THAT SERVES AHU-3.1S.

INSTALL ONE 25 HORSEPOWER RATED ABB VARIABLE SPEED DRIVE TO REPLACE THE EXISTING 20 HORSEPOWER RATED ABB DRIVE. THE DRIVE WILL BE FURNISHED BY THE

PROVIDE ONE 70-AMP RATED, 3-POLE CIRCUIT BREAKER IN PANELBOARD "M3C" TO SERVE NEW 25 HORSEPOWER RATED FAN MOTOR.

PROVIDE THREE #8 AWG THHN CONDUCTORS WITH ONE #10 AWG THHN GREEN GROUND WIRE IN 3/4" RMC CONDUIT FROM PANEL "M3C", THROUGH EXISTING STARTER AND NEW VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT-BOLT SPLICES AND HEAT OR COLD-SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS TYPE BOLTED CONNECTORS SHALL NOT BE USED).

- D2. AHU-3.2S: EXISTING 10 HORSEPOWER, 480-VOLT FAN MOTOR IS BEING REPLACED WITH A 15 HORSEPOWER MOTOR UNDER THIS CONTRACT. EXISTING 30-AMP 3-POLE CIRCUIT BREAKER IN PANEL "M3C" SHALL BE REMOVED AND REPLACED AS INDICATED IN NOTE R2 BELOW. EXISTING DISCONNECT SWITCH SHALL REMAIN IN PLACE BUT NEW FUSES SHALL BE PROVIDED AS INDICATED IN NOTE R2 BELOW. EXISTING RACEWAYS SHALL REMAIN IN PLACE AND BE RE-USED EXCEPT THAT EXISTING FLEXIBLE METAL RACEWAY CONNECTED TO MOTOR PECKERHEAD SHALL BE REMOVED AND REPLACED. DISCONNECT EXISTING FAN MOTOR, VARIABLE SPEED DRIVE, AND ALL ASSOCIATED POWER CONDUCTORS (BACK TO PANELBOARD "M3C").
- R2. <u>AHU-3.2S</u>:

PROVIDE THREE NEW FUSES IN EXISTING DISCONNECT SWITCH. FUSES SHALL BE CLASS RK5 AND SHALL BE SIZED PER THE MOTOR MANUFACTURER'S RECOMMENDATIONS.


PROVIDE ONE NEW NEMA SIZE 2, 3-POLE, 480-VOLT MOTOR STARTER WITH NEMA-1 ENCLOSURE TO REPLACE THE EXISTING FPE STARTER - COIL VOLTAGE SHALL MATCH THAT OF THE EXISTING FPE STARTER. PROVIDE THREE MELTING ALLOW THERMAL UNITS RATED FOR A 15 HORSEPOWER MOTOR IN STARTER.

INSTALL ONE 15 HORSEPOWER RATED ABB VARIABLE SPEED DRIVE TO REPLACE THE EXISTING 10 HORSEPOWER RATED ABB DRIVE. THE DRIVE WILL BE FURNISHED BY THE MECHANICAL CONTRACTOR.


PROVIDE ONE 40-AMP RATED, 3-POLE CIRCUIT BREAKER IN PANELBOARD "M3C" TO SERVE NEW 15 HORSEPOWER RATED FAN MOTOR.

PROVIDE THREE #10 AWG THHN CONDUCTORS WITH ONE #10 AWG THHN GREEN GROUND WIRE FROM PANEL "M3C", THROUGH NEW STARTER AND VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT-BOLT SPLICES AND HEAT OR COLD-SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS TYPE BOLTED CONNECTORS SHALL NOT BE USED).

- D3. AHU-3.3S: EXISTING 15 HORSEPOWER, 480-VOLT FAN MOTOR IS BEING REPLACED UNDER THIS CONTRACT. EXISTING RACEWAYS, 40-AMP 3-POLE CIRCUIT BREAKER IN PANEL "M3A", AND VARIABLE SPEED DRIVE SHALL REMAIN IN PLACE AND SHALL BE RE-USED. DISCONNECT EXISTING FAN MOTOR, FLEXIBLE METAL CONDUIT TO MOTOR PECKERHEAD, AND ALL ASSOCIATED POWER CONDUCTORS FROM RACEWAYS (BACK TO PANELBOARD "M3A"). NOTE THAT CONDUCTORS APPEAR TO BE ROUTED THROUGH EXISTING JOHNSON CONTROLS DSC-8500 PANELS - THIS POWER WIRING SHALL ALSO BE REMOVED/REPLACED.
- R3. AHU-3.3S: PROVIDE THREE #10 AWG THHN CONDUCTORS WITH ONE #10 AWG THHN GREEN GROUND WIRE FROM PANEL "M3A", THROUGH EXISTING JOHNSON CONTROLS DSC-8500 PANELS AND VARIABLE SPEED DRIVE, TO NEW FAN MOTOR (ALL POWER CONDUCTORS SHALL BE REPLACED). PROVIDE 3/4" FLEXIBLE METAL CONDUIT FOR FINAL RACEWAY CONNECTION TO MOTOR PECKERHEAD. PROVIDE SPLIT-BOLT SPLICES AND HEAT OR COLD-SHRINK BOOTS IN MOTOR PECKERHEAD FOR CONDUCTOR TERMINATIONS (POLARIS TYPE BOLTED CONNECTORS SHALL NOT BE USED).



THIRD FLOOR ELECTRICAL RENOVATION PLAN (NORTHWEST CORNER OF BUILDING)



THIRD FLOOR ELECTRICAL RENOVATION PLAN (SOUTHEAST CORNER OF BUILDING)

CAMPUS PLANNING AND CONSTRUCTION COLUMBIA, SC 29208

BEA

