

ADDENDUM TO
SPECIFICATIONS ENTITLED
'SPECIFICATIONS FOR
JONES PSC ROOF REPLACEMENT
UNIVERSITY OF SOUTH CAROLINA
COLUMBIA, SOUTH CAROLINA
PROJECT NO. H27-6094-Z"

ADDENDUM NO. 1

June 4, 2015

The Specifications and Drawings contained in the project manual entitled "Specifications for Jones PSC Roof Replacement, University of South Carolina, Project No. H27-6094-Z" are amended as follows:

SPECIFICATIONS

1. In Section 06100 ROUGH CARPENTRY, delete paragraphs 3.6 and 3.7 in their entirety.
2. In Section 07000 ROOFING PREPARATION, add the following to paragraph 3.8:
 - E. Fasten stair treads to curb using Simpson H2.5A hurricane clips or approved equal.
 - F. Secure hurricane clips using #8 stainless steel screws 1¼" or longer.
3. In Section 07552 SBS-MODIFIED BITUMINOUS MEMBRANE ROOFING, delete paragraph 2.3.A in its entirety and replace with the following:
 - A. Base Ply: ASTM D 5147 and D 6163, Type II, Grade S, SBS-modified asphalt sheet (or ASTM D6164, Type I, Grade S, Polyester) with glass fiber mat reinforcing, suitable for application method specified.
4. In Section 07552 SBS-MODIFIED BITUMINOUS MEMBRANE ROOFING, delete paragraph 2.3.B and sub-paragraph 1 in its entirety and replace with the following:
 - A. Cap Sheet: ASTM D 5147 and D 6163, Type II, Grade G, SBS-modified asphalt sheet ASTM D6164, Type I, Grade S, Polyester, with glass fiber mat reinforcing, granular surfaced, suitable for application method specified and as follows:
 1. Granule Color: White.
5. In section 07552 SBS-MODIFIED BITUMINOUS MEMBRANE ROOFING, delete paragraph 2.4.A in its entirety and replace with the following:
 - A. Backer Sheet: ASTM D 6163 (or ASTM D 6164, Grade S, Polyester), Grade S, Type I, glass-fiber-reinforced, SBS-modified asphalt sheet; smooth surfaced; suitable for application method specified.
6. In section 07552 SBS-MODIFIED BITUMINOUS MEMBRANE ROOFING, delete paragraph 2.4.B and sub-paragraph 1 in its entirety and replace with the following:
 - A. Flashing Sheet: ASTM D 6163 or ASTM D 6164, Grade G, Type I, polyester-reinforced, SBS-modified asphalt sheet; granular surfaced; suitable for torch application method, and as follows:
 1. Granular surfaced.

DRAWINGS

1. Delete Drawings T 100, R-100, R-101, R-200, R-201, R-202, R-203, R-204, R-205 and R-206 in their entirety and replace with attached drawings T-100 (Addendum No. 1), R-100 (Addendum No. 1), R-101 (Addendum No. 1), R-200 (Addendum No. 1), R-201 (Addendum No. 1), R-202 (Addendum No. 1), R-203 (Addendum No. 1), R-204 (Addendum No. 1), R-205 (Addendum No. 1) and R-206 (Addendum No. 1).

END OF ADDENDUM

Enclosures: T-100 (Addendum No. 1)
R-100 (Addendum No. 1)
R-101 (Addendum No. 1)
R-200 (Addendum No. 1),
R-201 (Addendum No. 1)
R-202 (Addendum No. 1)
R-203 (Addendum No. 1)
R-204 (Addendum No. 1)
R-205 (Addendum No. 1)
R-206 (Addendum No. 1)