



<u>NOTES:</u>

- 1. GENERAL: REUSE EXISTING DEVICE LOCATIONS WHERE NOTED ON E2.1, WHERE POSSIBLE.
- 2. INSTALL FLEX CONDUIT IN EXISTING HOLLOW STUD WALLS WHERE POSSIBLE TO CONCEAL SURFACE MOUNTED WIREMOLD. USE OF SURFACE WIREMOLD WILL NEED TO BE APPROVED PER INSTALLATION. REFERENCE DETAILS H&I/E0.1 FOR WIREMOLD INSTALLATION.
- 3. EXISTING FIRE ALARM PULL STATIONS ARE TYPICALLY INSTALLED GREATER THAN 48" AFF, LOWER NEW DEVICE BOX TO THE APPROPRIATE HEIGHT, PER DETAIL J/E0.1, AND REPAIR WALL AS REQUIRED. PROVIDE A FINISHED METAL COVER FOR EXISTING BOX, WITH BEVELED EDGES, PAINTED TO MATCH SURROUNDING AREAS.



L	PROJECT NO.		REVISION	DATE	BY
7	1280UB	⋖	ISSUE FOR REVIEW	1/4/13	ADV
	DATE	В	FINAL ISSUE FOR REVIEW	2/8/13)DV
	08.24.2012				
	DRAWN BY				
	TMP/JDV				
	CHECKED BY				
	an C				

LLJIING
TRE ALARM REPLACEMENT
C PROJECT NO. H34-I357

BUILDING
TH FIRE ALARM REPLAY

UNIVERSITY
MEDIA BU
IIPSTATE

SHEET NUMBER

E1.3

5 of 7 sheets