
STUDENT UNION HVAC REPLACEMENT USC SUMTER

SUMTER, SC PROJECT NUMBER H39-I322

LOCATION MAP



DESIGN CODES AND STANDARDS

PROJECT DESIGNED IN ACCORDANCE WITH:


- 1. INTERNATIONAL BUILDING CODE 2018 EDITION
- 2. INTERNATIONAL MECHANICAL CODE 2018 EDITION
 3. NATIONAL ELECTRICAL CODE 2017 EDITION
- 4. STATE FIRE MARSHALL, LATEST EDITION
- 5. INTERNATIONAL FIRE CODE 2018 EDITION
- 6. INTERNATIONAL ENERGY CONSERVATION CODE 2009 EDITION.

DRAWING INDEX GENERAL T1 TITLE SHEET **ARCHITECTURAL** REFLECTED CEILING PLAN **MECHANICAL** MD1 HVAC DEMOLITION FLOOR PLAN **HVAC RENOVATION FLOOR PLAN HVAC ROOF PLAN NOTES AND LEGEND SCHEDULES DETAILS STRUCTURAL** S1 PARTIAL ROOF FRAMING PLAN **ELECTRICAL ELECTRICAL NOTES AND LEGEND ELECTRICAL FIRST FLOOR DEMOLITION PLAN ELECTRICAL FIRST FLOOR RENOVATION PLAN** C SUMTER CHANICAL ATE PROJE US(ME(STA Swygert & Associates CONSULTING ENGINEERS OF



RENOVATION FLOOR PLAN

SCALE: 1/8" = 1'-0"





Swygert & Associates CONSULTING ENGINEERS


OF SHEET IN SET:

OF

USC SUMTER STUDENT UNION MECHANICAL MAINTENANCE RENOVATION STATE PROJECT NUMBER: H39-I322







CAMPUS PLANNING AND CONSTRUCTION COLUMBIA, SC 29208

of

OF

CONSULTING ENGINEERS DBA Swygert & Assoc., Ltd.
Post Office Box 11686
Columbia, S.C. 29211

Telephone: (803) 791-9300
Facsimile: (803) 791-0830
mail@swygert-associates.com

OF SHEET IN SET:

	LEGEND						
SYMBOL	DESCRIPTION						
├ □ ──	DRAIN LINE						
(A)100	TYPE "A" DIFFUSER, 100 CFM						
Û	THERMOSTAT						
<u>@</u>	CARBON DIOXIDE SENSOR						
FD	FIRE DAMPER						
RD	CEILING RADIATION DAMPER						
FSD	COMBINATION FIRE/SMOKE DAMPER W/ 120V ACTUATOR						
MBD	MANUAL OPPOSED BLADE BALANCING DAMPER						
MOD	MOTORIZED DAMPER						
\boxtimes	RECTANGULAR SUPPLY DUCTWORK						
\otimes	OVAL SUPPLY DUCTWORK						
	RETURN, EXHAUST, FRESH AIR DUCTWORK						
48x24	48"x24" RECTANGULAR DUCT						
48/24	48"x24" OVAL DUCT						

	VENTILATION	SCHEDULE	
AREA	VENTILATION RATE PER PERSON	VENTILATION RATE PER AREA	REMARKS
CORRIDORS	N/A	0.06 CFM / SQ. FT.	2
CLASSROOMS	10 CFM / PERSON	0.12 CFM / SQ. FT.	2
OFFICES/WORK RMS.	5 CFM / PERSON	0.06 CFM / SQ. FT.	2

1. PER TABLE 403.3, 2003 IMC. 2. PER ASHRAE STANDARD 62.1 - 2004.

GENERAL CONSTRUCTION NOTES

GENERAL CONSTRUCTION NOTES:

CEILINGS:

- REMOVE AND SALVAGE EXISTING CEILING TILE AND GRID AS REQUIRED TO INSTALL HVAC WORK AS SHOWN ON THE PLANS. RE-INSTALL EXISTING GRID AND TILE AFTER HVAC WORK IS COMPLETE.
- REPLACE DAMAGED CEILING GRID AND TILES TO MATCH EXISTING. DO NOT INSTALL OR RE-INSTALL NEW CEILING TILES ADJACENT TO EXISTING CEILING TILES. RELOCATE EXISTING CEILING TILES FROM OTHER ROOMS AS REQUIRED SO THAT THE ENTIRE CEILING OF EACH ROOM WILL EITHER HAVE NEW CEILING TILES OR EXISTING CEILING TILES TO PROVIDE A UNIFORM APPEARANCE IN EACH ROOM. SEE SPECIFICATIONS 09113 FOR CEILING TILE AND GRID.
- AT CORRIDORS, INSTALL CEILING GRID AT HEIGHT AS REQUIRED TO INSTALL DUCTWORK BETWEEN CEILING ASSEMBLY AND FLOOR STRUCTURE ABOVE. COORDINATE AND VERIFY FINAL CEILING HEIGHT WITH THE ENGINEER PRIOR TO INSTALLING CEILING GRID. MAINTAIN MINIMUM 9' CEILINGS.
- INSTALL FIRE ALARM DEVICES AS REQUIRED AND AS NOTED IN THE ELECTRICAL DRAWINGS. COORDINATE DEVICES WITH ELECTRICAL CONTRACTOR.
- WHERE DUCT OR TRANSFER DUCTS AND THROUGH WALL UNITS ARE REMOVED, PATCH WALL OPENINGS SMOOTH AND FLUSH WITH EXISTING ADJACENT WALL CONSTRUCTION.

ROOF CURBS INSTALLED SHALL BE SET DOWN DIRECTLY ON ROOF DECK AND ANCHORED PER STRUCTURAL DRAWINGS. ROOF FLASHING SHALL BE SEALED TO MATCH EXISTING ROOF. ROOF INSULATION AND CANT SHALL EXTEND UP SIDE OF CURB WITH MEMBRANE UP TO NAILER STRIP PER DETAIL ON SHEET M5.

CUTTING AND PATCHING NOTES

- 1. CUT IN-PLACE CONSTRUCTION TO PROVIDE FOR INSTALLATION OF OTHER COMPONENTS OR PERFORMANCE OF OTHER CONSTRUCTION, AND SUBSEQUENTLY PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.
- 2. EXISTING WARRANTIES: REMOVE, REPLACE, PATCH, AND REPAIR MATERIALS AND SURFACES CUT OR DAMAGED DURING INSTALLATION OR CUTTING AND PATCHING OPERATIONS, BY METHODS AND WITH MATERIALS SO AS NOT TO VOID EXISTING WARRANTIES.
- 3. TEMPORARY SUPPORT: PROVIDE TEMPORARY SUPPORT OF WORK TO BE CUT.
- 4. PROTECTION: PROTECT IN-PLACE CONSTRUCTION DURING CUTTING AND PATCHING TO PREVENT DAMAGE. PROVIDE PROTECTION FROM ADVERSE WEATHER CONDITIONS FOR PORTIONS OF PROJECT THAT MIGHT BE EXPOSED DURING CUTTING AND PATCHING OPERATIONS.
- 5. EXISTING UTILITY SERVICES AND MECHANICAL/ELECTRICAL SYSTEMS: WHERE EXISTING SERVICES/SYSTEMS ARE REQUIRED TO BE REMOVED, RELOCATED, OR ABANDONED, BYPASS SUCH SERVICES/SYSTEMS BEFORE CUTTING TO MINIMIZE OR PREVENT INTERRUPTION TO OCCUPIED AREAS.
- 6. CUTTING: CUT IN-PLACE CONSTRUCTION BY SAWING, DRILLING, BREAKING, CHIPPING, GRINDING, AND SIMILAR OPERATIONS, INCLUDING EXCAVATION, USING METHODS LEAST LIKELY TO DAMAGE ELEMENTS RETAINED OR ADJOINING CONSTRUCTION. IF POSSIBLE, REVIEW PROPOSED PROCEDURES WITH ORIGINAL INSTALLER; COMPLY WITH ORIGINAL INSTALLER'S WRITTEN RECOMMENDATIONS.
- 7. IN GENERAL, USE HAND OR SMALL POWER TOOLS DESIGNED FOR SAWING AND GRINDING, NOT HAMMERING AND CHOPPING. CUT HOLES AND SLOTS NEATLY TO MINIMUM SIZE REQUIRED, AND WITH MINIMUM DISTURBANCE OF ADJACENT SURFACES. TEMPORARILY COVER OPENINGS WHEN NOT IN USE.
- 8. FINISHED SURFACES: CUT OR DRILL FROM THE EXPOSED OR FINISHED SIDE INTO CONCEALED SURFACES.
- 9. CONCRETE AND MASONRY: CUT USING A CUTTING MACHINE, SUCH AS AN ABRASIVE SAW OR A DIAMOND-CORE DRILL. USE WET SAW TO MINIMIZE DUST.
- 10. MECHANICAL AND ELECTRICAL SERVICES: CUT OFF PIPE OR CONDUIT IN WALLS OR PARTITIONS TO BE REMOVED. CAP, VALVE, OR PLUG AND SEAL REMAINING PORTION OF PIPE OR CONDUIT TO PREVENT ENTRANCE OF MOISTURE OR OTHER FOREIGN MATTER AFTER CUTTING.
- 11. PROCEED WITH PATCHING AFTER CONSTRUCTION OPERATIONS REQUIRING CUTTING ARE COMPLETE.
- 12. PATCHING: PATCH CONSTRUCTION BY FILLING, REPAIRING, REFINISHING. CLOSING UP, AND SIMILAR OPERATIONS FOLLOWING PERFORMANCE OF OTHER WORK. PATCH WITH DURABLE SEAMS THAT ARE AS INVISIBLE AS PRACTICABLE. PROVIDE MATERIALS AND COMPLY WITH INSTALLATION REQUIREMENTS SPECIFIED IN OTHER SECTIONS, WHERE APPLICABLE.
- 13. EXPOSED FINISHES: RESTORE EXPOSED FINISHES OF PATCHED AREAS AND EXTEND FINISH RESTORATION INTO RETAINED ADJOINING CONSTRUCTION IN A MANNER THAT WILL MINIMIZE EVIDENCE OF PATCHING AND REFINISHING.
- 14. CLEAN PIPING, CONDUIT, AND SIMILAR FEATURES BEFORE APPLYING PAINT OR OTHER FINISHING MATERIALS.
- 15. FLOORS AND WALLS: WHERE WALLS OR PARTITIONS THAT ARE REMOVED EXTEND ONE FINISHED AREA INTO ANOTHER, PATCH AND REPAIR FLOOR AND WALL SURFACES IN THE NEW SPACE. PROVIDE AN EVEN SURFACE OF UNIFORM FINISH, COLOR, TEXTURE, AND APPEARANCE. REMOVE IN-PLACE FLOOR AND WALL COVERINGS AND REPLACE WITH NEW MATERIALS, IF NECESSARY, TO ACHIEVE UNIFORM COLOR AND APPEARANCE.
- 16. WHERE PATCHING OCCURS IN A PAINTED SURFACE, PREPARE SUBSTRATE AND APPLY PRIMER AND INTERMEDIATE PAINT COATS APPROPRIATE FOR SUBSTRATE OVER THE PATCH, AND APPLY FINAL PAINT COAT OVER ENTIRE UNBROKEN SURFACE CONTAINING THE PATCH. PROVIDE ADDITIONAL COATS UNTIL PATCH BLENDS WITH ADJACENT SURFACES.
- 17. CEILINGS: PATCH, REPAIR, OR REHANG IN-PLACE CEILINGS AS NECESSARY TO PROVIDE AN EVEN-PLANE SURFACE OF UNIFORM APPEARANCE.
- 18. EXTERIOR BUILDING ENCLOSURE: PATCH COMPONENTS IN A MANNER THAT RESTORES ENCLOSURE TO A WEATHERTIGHT CONDITION AND ENSURES THERMAL AND MOISTURE INTEGRITY OF BUILDING ENCLOSURE.
- 19. CLEANING: CLEAN AREAS AND SPACES WHERE CUTTING AND PATCHING ARE PERFORMED. REMOVE PAINT, MORTAR, OILS, PUTTY, AND SIMILAR MATERIALS FROM ADJACENT FINISHED SURFACES.

DI	ESIGN CONDITION	IS
SEASON	OUTSIDE	INSIDE
SUMMER	96' FDB / 78' FWB	75° FDB / 50-60% RH
WINTER	24° FDB	70. EDB

- VISIT SITE PRIOR TO BIDDING. THIS CONTRACTOR SHALL DETERMINE DIFFICULTY OF INSTALLATION AND REFLECT THIS IN HIS BIDDING. DO NOT
- EXISTING PIPE, DUCTWORK, CONDUIT, ETC THAT INTERFERES WITH THE
- 4. ALL PIPING AND DUCTWORK INSULATION SHALL BE RUN CONTINUOUSLY THROUGH FLOORS, ROOFS AND PARTITIONS.
- 5. ALL MECHANICAL ITEMS EXTENDING THROUGH WALLS AND ROOF SHALL BE
- 6. EXTEND ALL DRAIN LINES TO NEAREST ROOF DRAIN OR AS INDICATED SO ROUTED AS TO AVOID INTERFERENCE WITH PASSAGEWAYS AND MAINTENANCE. DRAINS FROM ROOF TOP UNITS SHALL BE TRAPPED PER STATIC PRESSURE REQUIREMENTS.
- 7. ALL PIPING SHALL BE SUPPORTED IN ACCORDANCE WITH THE SPECIFICATIONS AND FURTHER SUPPORTS OR HANGERS SHALL BE PROVIDED TO PREVENT WEIGHT OF PIPING BEING PLACED ON EQUIPMENT.
- 8. ALL DUCTWORK SPECIFIED TO BE LINED SHALL BE INCREASED IN SIZE TO
- 9. FIRE DAMPERS SHALL BE INSTALLED WHERE SHOWN ON PLANS, IN ALL FIRE
- 10. SPACE ABOVE CEILING TO BE USED AS RETURN AIR PLENUM WHERE DUCT IS NOT INDICATED ABOVE RETURN AIR GRILLES.
- 11. ALL OPEN END DUCTS SHALL HAVE 1/4-INCH MESH GALVANIZED SCREEN IN
- 12. PROVIDE FOR ACCESS TO ALL EQUIPMENT REQUIRING CLEANING OR
- 13. THIS CONTRACTOR SHALL PROVIDE ALL ITEMS OF MISCELLANEOUS STEEL AS
- OF NEW WORK, SHALL BE PERFORMED BY A CONTRACTOR NORMALLY EMPLOYED TO DO SUCH WORK. MECHANICAL CONTRACTOR SHALL NOT
- 15. THIS CONTRACTOR SHALL INCLUDE ALL CONTROL WIRING. DIVISION 26 WILL PROVIDE ALL POWER WIRING. ALL WIRING SHALL BE IN ACCORDANCE WITH NATIONAL ELECTRIC CODE. CONTROL WIRING SHALL BE CONCEALED WITHIN DIVISION 23. POWER WIRING AND FIRE ALARM CONNECTIONS SHALL BE BY
- 16. LOCATE ALL SPACE CONTROL INSTRUMENTS 4'-0" ABOVE FINISHED FLOOR.
- 17. CORRECT SETTINGS ON ALL BALANCING FITTINGS SHALL BE PERMANENTLY MARKED. PROVIDE ORANGE FLAGGING RIBBON ON EACH DAMPER HANDLE FOR EASY IDENTIFICATION.
- 19. ITEMS REMOVED UNDER THIS CONTRACT SHALL BECOME THE PROPERTY OF
- 20. THE HVAC SYSTEMS SHALL NOT BE OPERATED DURING HEAVY CONSTRUCTION OPERATIONS INCLUDING MASONRY, GYPSUM BOARD SANDING, HEAVY CLEANUP ACTIVITIES, OR OTHER ACTIVITIES THAT CREATE AIRBORNE PARTICLES OR DEBRIS. ALL SYSTEMS SHALL BE CLEAN OF CONSTRUCTION DEBRIS, DUST AND DIRT AT FINAL COMPLETION. DUCT CLEANING AND UNIT/COIL CLEANING


DI	ESIGN CONDITION	IS
SEASON	OUTSIDE	INSIDE
SUMMER	96' FDB / 78' FWB	75' FDB / 50-60% RH
WINTER	24. LDB	70. LDB

GENERAL NOTES

- SCALE DRAWINGS. THIS CONTRACTOR SHALL VERIFY ALL EXISTING ITEMS AND LOCATIONS IN THE FIELD.
- 2. ALL DUCTWORK LOCATIONS SHALL BE COORDINATED WITH WORK UNDER OTHER DIVISIONS OF THE SPECIFICATIONS TO AVOID INTERFERENCE.
- ROUTING OF NEW SYSTEMS SHALL BE RELOCATED. THIS CONTRACTOR SHALL INCLUDE THE COST OF SUCH IN HIS BID UNLESS NOTED OTHERWISE.
- FLASHED AND COUNTERFLASHED.

- ALLOW FOR LINER.
- PARTITIONS. BLADES SHALL BE LOCATED OUT OF AIRSTREAM.
- REMOVABLE FRAME.
- ADJUSTMENT.
- REQUIRED FOR INSTALLATION OF ALL MECHANICAL ITEMS.
- 14. REMOVAL AND REPLACEMENT OF CEILING, AS REQUIRED FOR INSTALLATION REMOVE AND REPLACE CEILINGS WITH HIS OWN FORCES.
- WALL. DUCT DETECTORS PROVIDED BY DIVISION 26 SHALL BE INSTALLED BY DIVISION 26. CONTROL WIRING FOR UNIT SHUTDOWN SHALL BE BY DIVISION

- 18. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR ANY NECESSARY DISMANTLING OF EQUIPMENT TO BE REMOVED.
- THE CONTRACTOR AND SHALL BE PROPERLY DISPOSED OF.
- SHALL BE PERFORMED IF REQUIRED.



Swygert & Associates

Telephone: (803) 791-9300 Facsimile: (803) 791-0830 mail@swygert-associates.com DBA Swygert & Assoc., Ltd. Post Office Box 11686 Columbia, S.C. 29211

NOV.

UNION NNCE REI

STI MAII CT

S HA

 $\supset \Sigma$

INING ICTION 9208

PLANI STRUC A, sc 29;

CAMPUS AND CONS

HEET IN SET:

 OF

CONSULTING ENGINEERS

OF

	VARIABLE VOLUME BOX SCHEDULE								
TAO	TRANE	AIR INLET	coo	LING		HEATING		MAX. A.P.D.	DEMARKS
TAG	MODEL	INCHES	MAX CFM	MIN CFM	CFM	KW	STAGES	IN. W.C.	REMARKS
1-1	VCEF	12	2,000	600	630	9.0	2	0.08	1,2,3
1-2	VCEF	12	1,600	480	525	6.5	2	0.05	1,2,3
1-3	VCEF	12	2,000	600	630	1.0	2	0.08	1,2,3
1-4	VCEF	6	400	120	170	2.0	1	0.14	1,2,3
1-5	VCEF	6	300	100	100	1.0	1	0.02	1,2,3
1-6	VCEF	6	300	100	170	2.0	1	0.02	1,2,3
1-7	VCEF	6	900	270	270	4.0	2	0.14	1,2,3
1-8	VCEF	10	1,000	300	560	8.0	2	0.03	1,2,3

- 1. PROVIDE HEATING COIL ON BOX DISCHARGE WITH 4'-0" STRAIGHT PLENUM BEFORE FITTINGS OR TAKEOFFS. 2. PROVIDE 1" FOIL FACED INSULATION, LINE FUSE, AND DOOR INTERLOCKING DISCONNECT SWITCH.
- 3. CONTROLS SHALL BE PROVIDED BY THE CONTROL CONTRACTOR AND FACTORY MOUNTED.

ROOFTOP VARIABLE AIR VOLUME UNIT SCHEDULE													
TAG TRANE		LAIDELOW LECT LEAN		EXHAUST FAN AIRFLOW ESP FAN		OUTDOOR AIR-CFM DX NET (EER	ELECTRIC HEAT — KW	REMARKS		
	MODEL NO.		IN. WG	H.P.	CFM	IN. WG	H.P.	AIN-CHW	EA DB/WB	LA BD/WB	<u> 1 </u>	HEAT - KW	
RTU-1	TED330	8,900	2.2	10	3,000	0.5	1	1,200	81.8/68.7	59.5/57.5	11.0	36	1–7

- 1. PROVIDE WITH CERTIFIED SEISMIC CURB, INTERNAL VIBRATION ISOLATION, ECONOMIZER, EXHAUST FAN WITH STATIC TRAC, VARIABLE FREQUENCY DRIVE ON SUPPLY FAN, ABD SHAFT GROUNDING RING.
- . PROVIDE MICROPROCESSOR CONTROLS TO OPERATE THE UNIT WHEN INSTRUCTED BY THE EMS. PROVIDE STAND ALONE CONTROLS INCLUDING DISCHARGE TEMPERATURE AND DUCT STATIC PRESSURE SENSORS. UNIT SHALL INCLUDE AUXILIARY CONTACTS FOR START
- AND STOP CONTROL FROM BUILDING MANAGEMENT SYSTEM. PROVIDE BACNET INTERFACE MODULE TO INTERFACE WITH OWNER'S EXISTING BUILDING MANAGEMENT SYSTEM.
- 4. PROVIDE STAINLESS STEEL CONDENSATE DRAIN PAN.
- 5. INSTALL DUCT SMOKE DETECTORS IN RETURN WIRED TO SHUT DOWN THE UNIT.
- 6. PROVIDE 1 YEAR PARTS AND LABOR WARRANTY AND 5 YEAR COMPRESSOR WARRANTY.
- 7. PROVIDE FACTORY STARTUP.

	AIR DISTRIBUTION SCHEDULE								
TAG	DESCRIPTION	MANUFACTURER	MODEL	FRAME	CFM	NECK SIZE	FACE SIZE	MAX NC	REMARKS
A	UNI-FLOW SUPPLY	PRICE	ASPD	LAY-IN	0-125	6ø	24×24	25	1,2
B	UNI-FLOW SUPPLY	PRICE	ASPD	LAY-IN	126-250	8ø	24x24	25	1,2
0	UNI-FLOW SUPPLY	PRICE	ASPD	LAY-IN	251-350	10ø	24x24	25	1,2
0	UNI-FLOW SUPPLY	PRICE	ASPD	LAY-IN	351-450	12ø	24×24	25	1,2
E	PERFORATED RETURN	PRICE	APDDR	LAY-IN	0-1000	22×22	24×24	25	1,2

PROVIDE WITH STANDARD WHITE FINISH. PROVIDE ALUMINUM OR ALUMINIZED STEEL CONSTRUCTION.

	PACKAGED TERMINAL UNIT SCHEDULE						
TAG	GE MODEL NO.	COOLING CAP MBH @ 80/67/95	HTG. CAP. —MBH 47°F AMB.	AUX. HT. –KW	CFM	EER/COP	REMARKS
TWU-1	AZ6SH12DAD	11.6	10.4	1.9	450	11.3/3.5	1,2

- 1. PROVIDE FIBERGLASS REINFORCED POLYESTER WALL SLEEVE, POLYCARBONATE ARCHITECTURAL GRILLE, SUBBASE, AND LINE CORD POWER KIT.
- 2. PROVIDE MANUAL POSITIVE CLOSING FRESH AIR VENT, FREEZE SENTINAL PROTECTION, AND INDOOR COIL FROST CONTROL.

	EXHAUST FAN SCHEDULE						
TAG	GREENHECK MODEL NO.	TYPE	CFM	ESP	MOTOR H.P./W.	SONES (MAX.)	REMARKS
EF-1	SP-A250	CEILING	210	0.375	83 W	3.8	1, 2
EF-2	SP-A250	CEILING	210	0.375	83 W	3.8	1, 2
EF-3	SP-A250	CEILING	210	0.375	83 W	3.8	1, 2
EF-4	SP-A250	CEILING	210	0.375	83 W	3.8	1, 2

PROVIDE WITH CEILING GRILLE, BACKDRAFT DAMPER, DISCONNECT SWITCH, AND SPEED CONTROL.
 INTERLOCK WITH LIGHT SWITCH, WIRED BY ELECTRICAL CONTRACTOR.

CAMPUS PLANNING AND CONSTRUCTION COLUMBIA, SC 29208

USC SUMTER STUDENT UNION MECHANICAL MAINTENANCE RENOVATION STATE PROJECT NUMBER: H39-I322


Carolina


Swygert & Associates

CONSULTING ENGINEERS

OF HEET IN SET: OF

SWYGERT AND ASSOCIATES, LTD. NO. C00227









Carolina

USC SUMTER STUDENT UNION MECHANICAL MAINTENANCE RENOVATION STATE PROJECT NUMBER: H39-1322


DBA Swygert & Assoc., Ltd.
Post Office Box 11686
Columbia, S.C. 29211

Telephone: (803) 791-9300
Facsimile: (803) 791-0830
mail@swygert-associates.com

Swygert & Associates CONSULTING ENGINEERS


OF HEET IN SET:

OF




ROOFTOP UNIT DETAIL

NO SCALE




RETURN GRILLE DETAIL

NO SCALE




ROOFTOP PIPE SUPPORT DETAIL

NO SCALE




CEILING DIFFUSER DETAIL

NO SCALE



CONDENSATE DRAIN DETAIL

NO SCALE



ELECTRICAL GENERAL NOTES

- 1. BRANCH CIRCUIT WIRING SHALL BE NO. 12 AWG UNLESS NOTED OTHERWISE. WHERE CONDUCTOR AND RACEWAY SIZE ARE SHOWN AT HOMERUN, SUCH SIZE SHALL BE USED FOR THE ENTIRE CIRCUIT. EXCEPTION: FINAL CONNECTION TO DEVICES, IN OUTLET BOXES, IS NOT REQUIRED TO BE LARGER THAN NO. 12 AWG.
- 2. 20A/120V BRANCH CIRCUITS EXCEEDING 100' IN LENGTH FROM PANEL TO FARTHEST DEVICE OR FIXTURE SHALL USE NO. 10 CONDUCTORS AND 3/4"C.
- 3. RACEWAYS SHALL BE INSTALLED CONCEALED IN NEW WALL CONSTRUCTION ABOVE CEILINGS, BELOW FLOOR, AND IN OTHER CAVITIES TO THE GREATEST EXTENT POSSIBLE. WHERE EXPOSED RACEWAYS MUST BE USED, LAYOUT RACEWAYS TO MINIMIZE THE NUMBER OF VERTICAL RUNS.
- 4. FEEDER AND BRANCH CIRCUITS ROUTING SHALL COMPLY WITH DETAILS ON DRAWINGS AND SHALL BE COORDINATED WITH THE WORK OF OTHER TRADES BEFORE AND DURING CONSTRUCTION.
- 5. REFER TO THE MECHANICAL DRAWINGS FOR PROJECT PHASING.
- 6. THE ARRANGEMENT, GROUPING, AND ROUTING OF BRANCH CIRCUITS SHALL BE PROVIDED AT THE CONTRACTOR'S DISCRETION IN ACCORDANCE WITH GENERALLY ACCEPTED PRACTICE FOR ELECTRICAL WORK, THE NATIONAL ELECTRICAL CODE REQUIREMENTS, LOCAL ORDINANCES.
- 7. A COMMON NEUTRAL SHALL NOT BE INSTALLED IN A HOMERUN FOR 2 OR 3 BRANCH CIRCUITS UNLESS DIRECTION IS PROVIDED BY THE ENGINEER IN WRITTING FOR A SPECIFIC APPLICATION.
- 8. MULTIPLE SINGLE-POLE BRANCH CIRCUITS (UP TO 3 HOTS, 3 NEUTRALS, 1 GROUND) RATED FOR 30-AMPS OR LESS MAY BE PULLED INTO A SINGLE RACEWAY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR SIZING THE RACEWAYS AND DERATING CONDUCTORS PER NEC ARTICLE 310.15.
- 9. A GROUND CONDUCTOR SHALL BE PROVIDED IN ALL RACEWAYS UNLESS NOTED OTHERWISE.
- 10. THE USE OF MC CABLE IS NOT ALLOWED.
- 11. SEAL ALL EXISTING AND NEW FIRE RATED WALL AND FLOOR PENETRATIONS IN THE CONSTRUCTION AREA

- 12. SEE MECHANICAL DRAWINGS FOR ALL LOCATIONS OF FIRE RATED WALLS.
- 13. WHEREVER ON THE ELECTRICAL DRAWINGS THE WORD "PROVIDE" IS USED, IT SHALL BE INFERRED TO MEAN "FURNISH AND INSTALL".
- 14. AREAS OF WORK EXIST FOR THIS PROJECT WHICH ARE NOT ACCESSIBLE OR HAVE LIMITED ACCESS DURING DESIGN. AS SUCH CONTRACTOR SHALL VERIFY ALL UTILITIES IN AREA OF WORK BEFORE DEMOLITION OF ANY SERVICE. ANY ELECTRICAL COMPONENTS NOT SHOWN SHALL BE IDENTIFIED AND THE ARCHITECT AND ENGINEER SHALL BE NOTIFIED AS SOON AS POSSIBLE. NO ELECTRICAL REWORK SHALL BE COMMENCED WITHOUT COORDINATION OF BOTH ARCHITECT AND ENGINEER.
- 15. IN AREAS WHERE THE EXISTING CEILINGS ARE NOT SLATED TO BE REMOVED, THE CONTRACTOR SHALL WORK THRU THE EXISTING CEILINGS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING ANY DAMAGED TILE OR GRID THAT IS A RESULT OF THEIR WORK.
 - SUPPORT ALL EXISTING CONDUITS AND JUNCTION BOXES ABOVE THE CEILING PER NEC IN THE CONSTRUCTION AREA.
- 16. REMOVE ALL ABANDONED CONDUIT, WIRE, AND COMMUNICATION CABLES ABOVE THE CEILING IN THE CONSTRUCTION AREA.
- 17. PROVIDE JUNCTION BOX COVER PLATES ON ALL EXISTING JUNCTION BOXES ABOVE THE CEILING IN THE CONSTRUCTION AREA.
- 18. WHERE INFORMATION SHOWN ON THESE DRAWINGS CONFLICTS WITH VERIFIED FIELD CONDITIONS, IT SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER
- 19. ALL ELECTRICAL EQUIPMENT TO BE REMOVED SHALL REMAIN THE PROPERTY OF THE OWNER. THE CONTRACTOR SHALL NOT DISPOSE OF ANY MATERIALS UNTIL RELEASED BY OWNER'S PROJECT MANAGER. MATERIALS THAT OWNER'S PROJECT MANAGER CHOOSES TO RETAIN SHALL BE DELIVERED BY THE CONTRACTOR TO A LOCATION DESIGNATED BY THE PROJECT MANAGER. ALL OTHER MATERIALS SHALL BE PROPERLY DISPOSED OF BY THE CONTRACTOR.
- 20. PROVIDE UPDATE, TYPED PANEL DIRECTORIES IN ALL PANELS AFFECTED BY THIS RENOVATION.

PANEL "M" 400 AMP, MAIN BREAKER GE TYPE "SCP" PLUS

PANEL "A" 225 AMP, M.L.O. GE TYPE "A" SERIES

PANEL "B" 100 AMP, M.L.O. GE TYPE "NLAB"

PANEL "C" 225 AMP, M.L.O. GE TYPE "NLAB"

PANEL "F" 225 AMP, M.L.O. GE TYPE "A" SERIES

EXISTING ELECTRICAL PANEL DESCRIPTIONS


EXISTING FIRE ALARM CONTROL PANEL (FACP) SIMPLEX 4020 SERIES

800 AMP, MAIN BREAKER GE TYPE "SCP" PLUS

	ELECTRICAL SYMBOL LEGEND
SYMBOL	DESCRIPTION
R	EXISTING DISCONNECT SWITCH TO BE REMOVED BY ELECTRICAL CONTRACTOR
E	EXISTING DISCONNECT SWITCH TO REMAIN IN PLACE
M	DISCONNECT SWITCH INTEGRAL WITH MECHANICAL EQUIPMENT
⇧	DISCONNECT SWITCH PROVIDED BY ELECTRICAL CONTRACTOR (100 AMP, 3-POLE, 240V, FUSIBLE, NEMA 3R)
2	DISCONNECT SWITCH PROVIDED BY ELECTRICAL CONTRACTOR (200 AMP, 3-POLE, 240V, FUSIBLE, NEMA 3R)
3	DISCONNECT SWITCH PROVIDED BY ELECTRICAL CONTRACTOR (400 AMP, 3—POLE, 240V, FUSIBLE, NEMA 3R)
0	DUCT TYPE SMOKE DETECTOR (FURNISHED BY ELECTRICAL CONTRACTOR; INSTALLED AND WIRED FOR FAN SHUTDOWN BY MECHANICAL CONTRACTOR; AND CONNECTED TO EXISTING FIRE ALARM CONTROL PANEL BY ELECTRICAL CONTRACTOR)
♦	DUCT TYPE SMOKE DETECTOR, MOUNTED IN EXISTING ACOUSTICAL TILE CEILING BELOW HVAC UNIT (PROVIDED BY ELECTRICAL CONTRACTOR)
	EXISTING ELECTRICAL PANEL TO REMAIN

ELECTRICAL DRAWING INDEX

- E1 ELECTRICAL SYMBOL LEGEND AND GENERAL NOTES
- E2 ELECTRICAL DEMOLITION PLAN
- E3 ELECTRICAL RENOVATION PLAN





CAMPUS PLANNING
AND CONSTRUCTION
COLUMBIA, SC 29208

USC SUMTER STUDENT UNION MECHANICAL MAINTENANCE RENOVATION STATE PROJECT NUMBER: H39-1322 arolina

EET: E1

1 OF 3

OF



USC SUMTER STUDENT UNION MECHANICAL MAINTENANCE RENOVATION STATE PROJECT NUMBER: H39-1322


Carolina

CAMPUS PLANNING AND CONSTRUCTION COLUMBIA, SC 29208

2 OF 3

SHEET IN SET:

2519A PLATT SPRINGS RD | WEST COLUMBIA, SC CONTACT: CLIFF STRINGFIELD CSTRINGFIELD@BEA-Consulting.com



CAMPUS PLANNING AND CONSTRUCTION COLUMBIA, SC 29208

USC SUMTER STUDENT UNION MECHANICAL MAINTENANCE RENOVATION STATE PROJECT NUMBER: H39-1322 Carolina

2519A PLATT SPRINGS RD | WEST COLUMBIA, SC

CONTACT: CLIFF STRINGFIELD

3 OF 3 SHEET IN SET: